SEMPERIT

TM30

Рукав маслобензостойкий напорно-всасывающий

Применение:

Рукав для наполнения и выпуска баков заправочных автомобилей и судов с неэтилированным топливом (EN228: 2012), с содержанием ароматических компонентов не более 50%

Подходит для индустриальных и дизельных масел (EN 590: 2010), жидкого топлива (51 603 части 1-5) и гидравлических масел на основе натуральных масел.

Температурный режим:

-40°C / +90°C (для масел +100°C).

Запас прочности:

3:1

Внутренний слой:

NBR, черный, гладкий, электропроводящий

Армирование:

Тканевая навивка, одна медная проволока, оцинкованная спираль из стальной проволоки (ID меньше 2 ½") и двойная оцинкованная спираль из стальной проволоки (ID больше 2 ½")

Наружный слой:

SBR/EPDM, черный, электроповодящий, износостойкий, озоно- и маслостойкий (согласно SAE J517: 2013), отпечаток текстильного бандажа

Обозначние:

Непрерывная желтая лента

"SEMPERIT (S) TM30 PETROLEUM / OIL S&D WP 10 BAR Made in Europe"



Article number	Internal-Ø in		Wall width	External-Ø	Work. pressure	Number of inserts	Bending radius	Weight approx.	Coil length
	mm	inch	in mm	in mm	(max.) bar		(min.) in mm	kg/m	(max.) m
48816 1350	13,0	1/2	5,0	23,0	10	2	35	0,35	40
48816 1650	16,0	3/8	5,0	26,0	10	2	40	0,50	40
48816 1950	19,0	3/4	5,0	29,0	10	2	45	0,60	40
48816 2550	25,0	1	5,0	35,0	10	2	55	0,70	40
48816 3050	30,0		5,0	40,0	10	2	60	0,80	40
48816 3250	32,0	1 1/4	5,0	42,0	10	2	65	0,90	40
48816 3550	35,0		5,0	45,0	10	2	75	1,00	40
48816 3850	38,0	1 1/2	5,0	48,0	10	2	80	1,10	40
48816 4050	40,0		5,0	50,0	10	2	100	1,15	40
48816 5155	50,8	2	5,5	61,8	10	2	130	1,30	40
48816 6055	60,0		5,5	71,0	10	2	150	1,80	40
48816 6360	63,0	2 1/2	6,0	75,0	10	2	180	2,00	40
56816 7060	70,0		6,0	82,0	10	2	330	2,40	40
56816 7660	76,0	3	6,0	88,0	10	2	350	2,55	40
56816 0270	101,6	4	7,0	115,4	10	2	400	3,90	40
56816 1385	127,0	5	8,5	144,0	10	2	600	5,00	40
56816 1690	152,4	6	9,0	170,4	10	2	800	7,60	40

Vacuum resistance up to -0.9 bar

Please note: Before using our products with new or untested media, or for applications that are not clearly indicated in the product information, written advice must be obtained from a specialist dealer or a Semperit application engineer. For safety reasons, all products must be inspected regularly for operational safety and replaced in the event of any damage (especially of the cover) or unusual signs of wear and tear. All products must be stored, handled and maintained in accordance with all our respective instructions and DIN 7716:1982. The information in our catalogue as well as each individual datasheet is subject to change at any time without notice since we are constantly developing and improving our products and due to constant technical developments after the latest release date of the catalogue and/or individual datasheets. In order to always have the latest product and safety information make sure you visit our website (www.semperflex.com) regularly or contact one of our specialist dealers or a Semperit application engineer. All contracts with Semperflex are exclusively subject to our general terms and conditions (available at www.semperitgroup.com). Additional important general information about the range, choice and safe use of our products can be found at our website (www.semperflex.com) and must be followed without exception.

Important notice: Our catalogue and any individual datasheet have been prepared with great care in order to provide you with all the information you need. The information contained therein is based on the latest state-of-the-art industrial technology and many years of experience and testing; whenever indicated for a certain product, we also confirm conformity with the resistance requirements of the media listed in ISO TR 7620: 2005(E). However, the individual conditions of storage, maintenance and use decisively affect the safe and durable use of each product. The quality and safety of our products as indicated in the catalogue or individual datasheets are therefore strictly subject to the continuous observance of all specifications and restrictions in our written product information and applicable laws and standards, the specifications regarding resistance to chemicals and our cleaning procedures. We reject any liability for safety issues or other consequences due to improper product choice, maintenance or handling (e.g. squashing, rupturing, stretching or filling with non-approved media). Our products must not be used in airplanes or other aircraft vehicles under any circumstance. Unless specified otherwise, all hoses are manufactured according to EN ISO 1307:2008.

Date: 21.09.2016

semperflex® INDUSTRIAL
A MEMBER OF THE SEMPERIT-GROUP